

# PCM-3618

# PCM-3640/3641

# PCM-3660

8-port RS-422/485 High-speed Module

4-port RS-232 High-speed Module

Jumperless Ethernet Module



## Features

- Automatic RS-485 data flow control
- Shared IRQ settings for each ports
- LED indicators: TX, RX
- Supports Windows® 98/2000/XP
- Supports WinCE 4.2, 5.0
- Powerful and easy-to-use utility (ICOM Tools)

## Specifications

### General

- Card Interface PC/104
- Certifications CE
- Connectors 8 x DB9-M
- Ports 8
- Power Consumption +5 V @ 650 mA

### Communications

- Data Bits 5, 6, 7, 8
- I/O Address Range 0 x 000 ~ 0 x 3F8
- IRQ 3, 4, 5, 6, 7, 9, 10, 11, 12, 15
- Parity None, even and odd
- Data Signals RS-422: TxD+, TxD-, RxD+, RxD-, CTS+, CTS-, RTS+ and RTS-  
RS-485: DATA+, DATA-, CTS+, CTS-
- Speed 50 bps ~ 921.6 kbps
- Stop Bits 1, 1.5, 2
- Termination Resistor 120 Ω

### Protection

- EFT Protection 1,000 V<sub>DC</sub>

### Environment

- Humidity (Operating) 0 ~ 90 % RH
- Operating Temperature 0 ~ 65° C (32 ~ 149° F)  
(IEC-68-1-1, 2)
- Storage Temperature -25 ~ 80° C (-13 ~ 176° F)

## Ordering Information

- PCM-3618-A 8-port RS-422/485 High-Speed Module

## Features

- Transmission speeds up to 460 kbps (PCM-3641)
- Shared IRQ settings for each of 4 RS-232 ports (PCM-3641)
- Standard PC ports: COM1, COM2, COM3, COM4 compatible
- Supports Windows® 98/2000/XP
- Supports WinCE 3.0, 4.2, 5.0
- Powerful and easy-to-use utility (ICOM Tools)

## Specifications

### General

- Card Interface PC/104
- Certifications CE
- Connectors 4 x DB9-M
- Ports 4
- Power Consumption +5 V @ 200 mA (Typical);  
+5 V @ 250 mA (Max.)

### Communications

- Data Bits 5, 6, 7, 8
- Data Signals RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- I/O Address Range 0 x 0200 ~ 0 x 03F8
- IRQ 3, 4, 5, 6, 7, 9, 10, 11, 12, 15
- Parity None, even and odd
- Speed 50 bps ~ 460.3 kbps (PCM-3641)  
50 bps ~ 115.2 kbps (PCM-3640)
- Stop Bits 1, 1.5, 2

### Environment

- Humidity (Operating) 0 ~ 90 % RH
- Operating Temperature 0 ~ 65° C (32 ~ 149° F)  
(IEC-68-1-1, 2)
- Storage Temperature -25 ~ 80° C (-13 ~ 176° F)

## Ordering Information

- PCM-3640-A 4-port RS-232 Module
- PCM-3641-A 4-port RS-232 High-speed Module

## Features

- Automatically detects 8-bit or 16-bit
- AUI connector supports external MAUs
- Onboard 32 KB buffer for multi-packages

## Specifications

### General

- Boot ROM Address C0000, C8000, D0000, or D8000H
- Card Interface PC/104
- Certifications CE
- Connectors 1 x PC/104 stackthrough  
1 x 10Base-T (RJ-45)  
1 x 16-pin insulation displacement connector for AUI1
- Power Consumption +5 V @ 400 mA max

### Communications

- Data Bus 8-bit, 16-bit, or auto-sending
- I/O Address 200, 220, 240, 260, 280, 2A0, 2C0, 300, 320, 340, 380, 3A0
- IRQ 3,4,5,9, 10, 11, 12 or 15
- Standard IEEE 802.3 10 Mbps CSMA/CD 10Base-T Transceiver

## Ordering Information

- PCM-3660-C1 Jumperless Ethernet Module